



MATERIAL SAFETY DATA SHEET

Material: **Portland Cement**

Section I - Identification

Supplier:

Name: Holcim (US) Inc.
Address: 6211 N. Ann Arbor Road
 Dundee, MI 48131
Telephone: 800-854-4656

Emergency Contact Information: (CHEMTREC)
 Health 1-800-424-9300
 Transportation 1-800-424-9300

Product Codes: Portland Cement Type I, IA, II, III, IV, V, White Cement. CSA Type 10, 20, 30, 40, & 50. This MSDS covers many products. Individual constituents will vary.

Formula: This product consists of finely ground Portland cement clinker mixed with a small amount of calcium sulfate (gypsum).

Chemical Family: Chemical compounds. Calcium silicate components and other calcium compounds containing iron and aluminum make up the majority of this product.

Chemical Name and Synonyms: Portland cement. Portland cement is also known as hydraulic cement.

Section II - Components

Hazardous Ingredients

Component (%)	CAS No.	OSHA PEL (8-hour TWA)	ACGIH TLV-TWA (2002)
Tri-calcium silicate (20-70)	12168-85-3	see Nuisance Dust PEL	see Nuisance Dust TLV
Di-calcium silicate (10-60)	10034-77-2	see Nuisance Dust PEL	see Nuisance Dust TLV
Tetra-calcium- alumino-ferrite (5-15)	12068-35-8	see Nuisance Dust PEL	see Nuisance Dust TLV
Calcium sulfate (2-10)	---	see Nuisance Dust PEL	see Nuisance Dust TLV
Tri-calcium Aluminate (1-15)	12042-78-3	see Nuisance Dust PEL	see Nuisance Dust TLV
Magnesium oxide (0-4)	1309-48-4	see Nuisance Dust PEL	see Nuisance Dust TLV
Nuisance Dusts	---	15 mg/m ³ (total dust); 5 mg/m ³ (respirable dust)	10 mg/m ³ (total dust); 3 mg/m ³ (respirable dust)
Crystalline Silica (Quartz) * (0-1%)	14808-60-7	10 mg/m ³ /percent silica + 2 (respirable dust) 30 mg total dust/m ³ /percent silica + 2 (total dust)	0.10 mg/m ³
Hexavalent Chromium (measured as chromic acid and chromates)	18540-29-9	(100 mg/m ³)	

Trace constituents: Portland Cement has a variable composition depending upon the cementitious products produced in the cement kiln. Small amounts of naturally occurring, but potentially harmful, chemical compounds might be detected during chemical analysis. These trace compounds might include free crystalline silica, potassium and sodium compounds; heavy metals including cadmium, chromium, nickel and lead; and organic compounds. Other trace constituents may include calcium oxide (also known as free lime or quick lime).

Section III - Hazards Identification

Emergency Overview

Portland cement is a light gray powder that poses little immediate hazard. A single short-term exposure to the dry powder is not likely to cause serious harm. However, exposure to wet portland cement can cause serious, potentially irreversible tissue (skin or eye) destruction in the form of chemical (caustic) burns or an allergic reaction. The same type of tissue destruction can occur if wet or moist areas of the body are exposed for sufficient duration to dry portland cement.

Potential Health Effects

- **Relevant Routes of Exposure:** Eye contact, skin contact, inhalation, and ingestion
- **Effects resulting from eye contact:** Exposure to airborne dust may cause immediate or delayed irritation or inflammation.

Eye contact with larger amounts of dry powder or splashes of wet Portland cement may cause effects ranging from moderate eye irritation to chemical burns and blindness. Such exposures require immediate first aid (see section IV) and medical attention to prevent significant damage to the eye.

- **Effects resulting from skin contact:** Discomfort or pain cannot be relied upon to alert a person to a hazardous skin exposure. Consequently, the only effective means of avoiding skin injury or illness involves minimizing skin contact, particularly contact with wet cement. Exposed persons may not feel discomfort until hours after the exposure has ended and significant injury has occurred. Exposure to dry Portland cement may cause drying of the skin with consequent mild irritation or more significant effects attributable to aggravation of other conditions. Dry portland cement contacting wet skin or exposure to moist or wet portland cement may cause more severe skin effects including thickening, cracking or fissuring of the skin. Prolonged exposure can cause severe skin damage in the form of (caustic) chemical burns. Some individuals may exhibit an allergic response (e.g., allergic contact dermatitis) upon exposure to portland cement, possibly due to trace amounts of chromium. The response may appear in a variety of forms ranging from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with the product. Other persons may experience this effect after years of contact with portland cement products.
- **Effects resulting from inhalation:** Portland cement contains small amounts of free crystalline silica. Prolonged exposure to respirable free crystalline silica can aggravate other lung conditions and cause silicosis, a disabling and potentially fatal lung disease and/or other diseases. Risk of injury or disease depends on duration and degree of exposure. (Also see "Carcinogenic potential" below.) Exposure to Portland cement may cause irritation to the moist mucous membranes of the nose, throat, and upper respiratory system. It may also leave unpleasant deposits in the nose.
- **Effects resulting from ingestion:** Although small quantities of dust are not known to be harmful, ill effects are possible if larger quantities are consumed. Portland cement should not be eaten.
- **Carcinogenic potential:** NTP, OSHA, or IARC has not listed Portland cement as a carcinogen. It may, however, contain trace amounts of substances listed as carcinogens by these organizations. Crystalline silica, which is present in Portland cement in small amounts, has been listed by IARC and NTP as a known human carcinogen (Group I) through inhalation. Hexavalent chromium is listed by IARC, EPA, NTP and OSHA as Group I known carcinogen by inhalation.
- **Medical conditions which may be aggravated by inhalation or dermal exposure:**
 - Pre-existing upper respiratory and lung diseases
 - Unusual (hyper) sensitivity to hexavalent chromium (chromium⁺⁶) salts.

Section IV - First Aid

Eyes: Immediately flush eyes thoroughly with water. Continue flushing eye for at least 15 minutes, including under lids, to remove all particles. Call physician immediately.

Skin: Wash skin with cool water and pH-neutral soap or a mild detergent. Seek medical treatment in all cases of prolonged exposure to wet cement, wet cement mixtures, wet concrete liquids from fresh cement products, or prolonged wet skin exposure to dry cement.

Inhalation of Airborne Dust: Remove to fresh air. Seek medical help if coughing or other symptoms do not subside. (Inhalation of gross amounts of portland cement requires immediate medical attention.)

Ingestion: Do not induce vomiting. If conscious, have the victim drink plenty of water and call a physician immediately.

Section V - Fire & Explosion Data

Flash point:	None	Auto ignition temperature:	Not Combustible
Lower Explosive Limit:	None	Upper Explosive Limit:	None
Extinguishing media:	Not Combustible	Unusual fire & explosion hazards	None
Hazardous combustion products:	None		

Special fire fighting procedures: None. (Although portland cement poses no fire-related hazards, a self-contained breathing apparatus is recommended to limit exposure to combustion products when fighting any fire.)

Section VI - Accidental Release Measures

Collect dry material using a scoop. Avoid actions that cause dust to become airborne. Avoid inhalation of dust and contact with skin. Wear appropriate personal protective equipment as described in Section VIII.

Scrape up wet material and place in an appropriate container. Allow the material to "dry" before disposal. Do not attempt to wash portland cement down drains.

Dispose of waste material according to local, state, and federal regulations.

Section VII - Handling & Storage

Keep portland cement dry until used. Normal temperatures and pressures do not affect the material. Promptly remove dusty clothing or clothing which is wet with cement fluids and launder before reuse. Wash thoroughly after exposure to dust or wet cement mixtures or fluids.

Section VIII - Exposure Control/Personal Protection

Skin Protection: Prevention is essential to avoiding potentially severe skin injury. Avoid contact with unhardened wet portland cement products. If contact occurs, promptly wash affected area with soap and water. Where prolonged exposure to unhardened portland cement products might occur, wear impervious clothing and gloves to prevent skin contact. Where required, wear sturdy boots that are impervious to water to eliminate foot and ankle exposure. Do not rely on barrier creams; barrier creams should not be used in place of impervious gloves and clothing. Periodically wash areas contacted by dry portland cement or wet cement or concrete with a pH neutral soap. Wash again at the end of the work. If irritation occurs, immediately wash the affected area and seek treatment. If clothing becomes saturated with wet concrete, it should be removed and replaced with clean, dry clothing.

Respiratory protection: Avoid actions that cause dust to become airborne. Use local or general ventilation to control exposures below applicable exposure limits. Use NIOSH/MSHA-approved (under 30 CFR 11) or NIOSH-approved (under 42 CFR 84) respirators in poorly ventilated areas, if an applicable exposure limit is exceeded, or when dust causes discomfort or irritation. (Advisory: Respirators and filters purchased after July 10, 1998, must be certified under 42 CFR 84.)

Ventilation: Use local exhaust or general dilution ventilation to control exposure within applicable limits.

Eye Protection: In conditions where user may be exposed to splashes or puffs of cement, wear safety glasses with side shields or goggles. In extremely dusty or unpredictable environments, wear unvented or indirectly vented goggles to avoid eye irritation or injury. Contact lenses should not be worn when working with portland cement or fresh cement products.

Section IX - Physical & Chemical Properties

Appearance:	Gray or white powder	Vapor Pressure:	Not applicable
Odor:	No distinct odor	Vapor density:	Not applicable
Physical state:	Solid (powder)	Boiling point:	Not applicable (i.e., > 1000 ° C)
pH (in water):	12 to 13	Melting point:	Not applicable
Solubility in water:	Slightly (0.1 to 1.0%)	Specific gravity (H ₂ O = 1.0):	3.15
Evaporation Rate:	Not applicable		

Section X - Stability & Reactivity

Stability:	Stable.
Incompatibility:	Wet portland cement is alkaline. As such it is incompatible with acids, ammonium salts, and aluminum metal.
Conditions to avoid:	Unintentional contact with water.
Hazardous decomposition:	Will not spontaneously occur. Adding water produces (caustic) calcium hydroxide as a result of hydration.
Hazardous polymerization:	Will not occur.

Section XI - Toxicological Information

For a description of available, more detailed toxicological information, contact Holcim (US) Inc. (in Section I).

Section XII - Ecological Information

Ecotoxicity:	No recognized unusual toxicity to plants or animals
Relevant physical and chemical properties:	See Sections IX & X

Section XIII - Disposal

Dispose of waste material according to local, state, and federal regulations. (Since portland cement is stable, uncontaminated material may be saved for future use.) Dispose of bags in an approved landfill or incinerator.

Section XIV - Transportation Data

Hazardous materials description/proper shipping name:	Portland cement is not hazardous under U.S. Department of Transportation (DOT) regulations
Hazard class:	Not applicable
Identification class:	Not applicable
Required label text:	Not applicable
Hazardous substances/reportable quantities (RQ):	Not applicable

Section XV - Other Regulatory Information

Status under USDOL-OSHA Hazard Communication Rule, 29 CFR 1910.1200:	<i>Portland cement is considered a "hazardous chemical" under this regulation, and should be part of any hazard communication program.</i>
Status under CERCLA/Superfund, 40 CFR 117 and 302:	<i>Not listed.</i>
Hazard Category under SARA (Title III), Sections 311 & 312:	<i>Portland cement qualifies as a "hazardous substance" with delayed health effects.</i>
Status under SARA (Title III) Section 313:	<i>Not subject to reporting requirements under section 313.</i>
Status under TSCA (as of May 1997):	<i>Some substances in portland cement are on the TSCA inventory list.</i>
Status under the Federal Hazardous Substances Act:	<i>Portland cement is a "hazardous substance" subject to statutes promulgated under the subject act.</i>
Status under California Proposition 65:	<i>Portland cement contains chemicals (trace metals), including silica and hexavalent chromium, known to the State of California to cause cancer, birth defects or other reproductive harm. California law requires the manufacturer to give the above warning in the absence of definitive testing to prove that the defined risks do not exist.</i>
Status under Canadian Environmental Protection Act:	<i>Not listed.</i>
Workplace Hazardous Material Information System (Canada):	<i>Portland cement is considered to be a hazardous material under the Hazardous Product Act as defined by the Controlled Products Regulations (Class E - Corrosive Material) and is therefore subject to the labeling and MSDS requirements of the Workplace Hazardous Materials Information System (WHMIS).</i>

Section XVI - Other Information

Approved by: Susan Diehl, Vice President

Revision Date: April 3, 2003

Other important information: Portland cement should only be used by knowledgeable persons. While the information provided in the material safety data sheet is believed to provide a useful summary of the hazards of portland cement as it is commonly used, the sheet cannot anticipate and provide all of the information that might be needed in every situation. Inexperienced product users should obtain proper training before using this product.

A key to using the product safely requires the user to recognize that portland cement chemically reacts with water, and that some of the intermediate products of this reaction (that is, those present while a portland cement product is "setting") pose a more severe hazard than does portland cement itself. These hazards include potential injuries to eyes and skin.

The data furnished in this sheet do not address hazards that may be posed by other materials mixed with portland cement to produce portland cement products. Users should review other relevant material safety data sheets before working with this portland cement or with portland cement products, including, for example, portland cement concrete.

SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THERE OF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HOLCIM (US) INC., EXCEPT THAT THE PRODUCT SHALL CONFORM TO CONTRACTED SPECIFICATIONS.